

PATENT ABSTRACTS OF JAPAN

(11)Publication number : **10-237468**
(43)Date of publication of application : **08.09.1998**

(51)Int.Cl. C10L 1/04
C10L 1/18

(21)Application number : **09-056837** (71)Applicant : **SANYO CHEM IND LTD**
(22)Date of filing : **24.02.1997** (72)Inventor : **NAKADA YOSHIRO**
NOMURA TOMIO
HIRONAGA HIDEO

(54) FUEL OIL COMPOSITION**(57)Abstract:**

PROBLEM TO BE SOLVED: To provide a fuel oil composition having stable improved low- temperature flowability.

SOLUTION: A major proportion of petroleum middle and/or heavy distillate fuel base oil containing 0.05 to below 0.8wt.% 25C or higher n-paraffins and a content of a wax which deposits at a temperature lower than the cloud point by 10°C of below 6wt.% is further mixed with an ethylene/vinyl acetate (5-40 wt.%)/neononane (1-25wt.%) and/or vinyl neodecanoate copolymer having a number-average molecular weight of 500-5,000 and a molecular weight distribution of 4.0 or below and optionally an ethylene/vinyl acetate copolymer- unsaturated dicarboxylic acid ester adduct.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office